

Derek Marshall Lighting

Chandelier mounting Instructions

Do not exceed the lamp wattage as shown on the fixture

Consult a qualified electrician to ensure correct branch circuit conductor. This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and hazards involved.

Note: The important safeguards and instructions appearing on this page are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors which cannot be built into any product. These factors must be supplied by those installing and operating this fixture.

1. Remove all materials from packing and set on a non-scratch level surface. Please handle the tubular mounting assembly with care. Avoid dropping or bumping. Please read the note below regarding the small drop tube. Do not misplace the plastic lock rings that hold the glass elements in place.
2. Thread the two black and white supply wires coming from the cluster body through the drop tube assembly and screw the drop tube assembly onto the cluster body tightly by hand. Make sure the plastic grommets on each end of the tube remain in place. **Ensure that the swivel mount is at the top of the drop tube and attaches to the ceiling box by way of the canopy (see photo on right).**
3. Shut off power to the electrical box at the circuit breaker box. Attach fixture bracket to the electric box by means of two 8-32 screws. Make sure the two screws provided extend at least an inch beyond the bracket. Again, make sure the swivel mount is at the top end of the tube, not the bottom.
4. Attach canopy cover to the swivel on the end of the drop tube using the lock washer and nut provided. Tighten securely.
5. Holding the drop tube and canopy assembly, attach the fixture wires to the supply wires using appropriate wire nuts ensuring black goes to black and white to white. (Wire nuts are usually supplied by the electrician who installed the box. If you need additional wire nuts, please contact us.)
6. Slide canopy up and onto the mounting screws. Apply the two acorn nuts and tighten until the canopy is snug against the ceiling. Please ensure that the excess electrical wires are safely pushed back into the box before tightening. Make sure the swivel allows some movement of the tube.
7. Slip the glass lens onto the threaded bulb holder and apply the shade rings snugly to attach the glass lens assembly.
8. Installation is now complete. Install bulbs, turn on the power.

Note: The drop tubes for the individual glass elements are able to be turned a few degrees left or right in order to ensure that the assemblies all hang vertical and true. They will either tighten or loosen by several degrees without danger of their coming undone. Please use caution and do not unscrew more than a few degrees to attain a vertical position after the fixture is installed. It is helpful to have another person assist with the installation process.

Note: *the glass lens is not installed until the drop tube assembly is attached to the ceiling.*

For help with these directions please call 603-284-7000



Attaching drop tube assembly to the electrical box. Note the two bolts extending from the bracket. Canopy with drop tube attached is on the left and the fixture wires are connected to the supply wires by the wire nuts. Be sure to use the toothed locknut. Note also that the swivel lies right below the canopy.



Glass lens assembly attached to drop tube by the threaded plastic rings.