

Derek Marshall Lighting

Pendant with drop tube mounting Instructions

Consult a qualified electrician to ensure correct branch circuit conductor. This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and hazards involved.

Note: The important safeguards and instructions appearing on this page are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors which cannot be built into any product. These factors must be supplied by those installing and operating this fixture.

1. Remove all materials from packing and set on a non-scratch level surface. It is helpful to have another person assist with the installation process. *Note: the glass lens is not installed until the drop tube assembly is attached to the ceiling.*
2. Shut off power to the electrical box at the circuit breaker box. Attach fixture bracket to the electric box by means of the two 8-32 screws provided. Make sure the two bolts extend at least an inch beyond the bracket.
4. Attach canopy cover to the swivel on the end of the drop tube using the lock washer and nuts provided. Tighten securely.
5. Holding the drop tube and canopy assembly, attach the fixture wires to the supply wires using appropriate wire nuts ensuring black goes to black and white to white.
6. Slide canopy up and onto the mounting screws. Apply the two acorn nuts and tighten until the canopy is snug against the ceiling. Please ensure that the excess electrical wires are safely pushed back into the box before tightening..
7. Remove shade ring from the bulb holder unit on the end of the drop tube. Slip the glass lens onto the threaded bulb holder and reapply the shade ring snugly to attach the glass lens assembly. Installation is now complete. Install bulb, turn on the power.



Fixture bracket attached to electrical box. Note the two bolts extending from the bracket. Canopy with drop tube attached is on the left and the fixture wires are connected to the supply wires by the wire nuts. Be sure to use the toothed locknut under the hex nut attaching the canopy to the drop tube assembly.

Wiring complete with the canopy/drop tube assembly attached to the fixture bracket by means of the acorn nuts



Remove retainer ring from bulb holder



Glass lens assembly held in place by the retainer ring. Installation is complete ready for bulb and power to be turned on

Do not exceed the lamp wattage as shown on the fixture

In the event of difficulties, call Derek Marshall Lighting at 800-497-3891